


LINEAR 2 Series




*THIS FIXTURE MUST BEEN
INSTALLED WITH THIS
ACCESSORIES:

Occupancy Sensor



Emergency Battery
STB41A-08WLi-55
8W 900lm 90min
(Sold separately)



FEATURES


Voltage Range	120 ~ 277 VAC / 120 - 347 VAC
Frequency Range	50 ~ 60 Hz
Power Factor	>0,95
Efficiency	>130 lm/W
Lifetime	>100 000 h
Operating Temperature	-20°C/-4°F to 50°C /122°F
Installation	Surface / Suspended

DIMENSIONS

Length, in. mm)



Height and width, inch(mm)



CONFIGURATION

MODEL	POWER	OPTICS	CCT	CRI	DRIVER	ACCESSORIES	RAL COLOR
ST04 Serie 1	25W	120D 120°	35K 3500K	7 70	27RE 120-277 VAC. Dim 0-10V.	SE Sensor	W White
	30W		40K 4000K			EB Emergency Battery	
	40W		50K 5000K				

REFERENCES

References	3CCTK	
	Lumens	lm / w
ST04-25W-120D-3CCTK8-27RE-WH	> 3250	>130
ST04-30W-120D-3CCTK8-27RE-WH	> 3900	>130
ST04-40W-120D-3CCTK8-27RE-WH	> 5200	>130